

## ORDERING EXAMPLE DISC PACK COUPLINGS

ORDERING EXAMPLE	LP1	700	D	154	25	57.15	XX
Model	●						Special designation only (e.g. special bore diameter tolerances, balancing, etc.). Contact R+W for more information
Size		●					
Type (S or D)			●				
Overall length (mm)				●			
Bore diameter Ø D1 H7					●		
Bore diameter Ø D2 H7						●	
For custom features place an XX at the end of the part number and describe the special requirements (e.g. LP1 / 700 / D / 154 / 25 / 57.15 / XX - balanced for 8,000 rpm)							

ORDERING EXAMPLE	LP2	500	170	25.4	48	XX
Model	●					Special designation only (e.g. special bore diameter tolerances, balancing, etc.). Contact R+W for more information.
Size		●				
Overall length (mm)			●			
Bore diameter Ø D1 H7				●		
Bore diameter Ø D2 H7					●	
For custom features place an XX at the end of the part number and describe the special requirements (e.g. LP2 / 500 / 170 / 25.4 / 48 / XX - balanced for 10,000 rpm)						

ORDERING EXAMPLE	LP4	6000	D	239	55	80	XX
Model	●						Special designation only (e.g. special bore diameter tolerances, balancing, etc.). Contact R+W for more information.
Size		●					
Type (S or D)			●				
Overall length (mm)				●			
Bore diameter Ø D1 H7					●		
Bore diameter Ø D2 H7						●	
For custom features place an XX at the end of the part number and describe the special requirements (e.g. LP4 / 6000 / D / 239 / 55 / 80 / XX - F7 bore tolerance on D2)							

ORDERING EXAMPLE	LP3	6000	321	50.8	75	XX
Model	●					Sonderanfertigungen (z.B. andere Gesamtlänge) on request möglich.
Size		●				
Overall length (mm)			●			
Bore diameter Ø D1 H7				●		
Bore diameter Ø D2 H7					●	
For custom features place an XX at the end of the part number and describe the special requirements (e.g. LP3 / 6000 / 321 / 50.8 / 75 / XX - F7 bore tolerance on D2)						

ORDERING EXAMPLE	LP5	700	S	133	25.4	40	XX
Model	●						Special designation only (e.g. special bore diameter tolerances, balancing, etc.). Contact R+W for more information.
Size		●					
Type (S or D)			●				
Overall length (mm)				●			
Bore diameter Ø D1 H7					●		
Bore diameter Ø D2 H7						●	
For custom features place an XX at the end of the part number and describe the special requirements (e.g. LP5 / 700 / S / 133 / 25.4 / 40 / XX - balanced to 10,000 rpm)							

## ORDERING EXAMPLE DISC PACK COUPLINGS

ORDERING EXAMPLE	LPH	700	D	172	25.4	40	XX
Model	●						Special designation only (e.g. special bore diameter tolerances, balancing, etc.). Contact R+W for more information.
Size		●					
Type (D)			●				
Overall length (mm)				●			
Bore diameter Ø D1 H7					●		
Bore diameter Ø D2 H7						●	
For custom features place an XX at the end of the part number and describe the special requirements (e.g. LPH / 700 / D / 172 / 25.4 / 40 / XX - balanced to 8,000 rpm)							

ORDERING EXAMPLE	LPZ	500	XX
Model	●		Special designation only (e.g. balancing, materials, etc.). Contact R+W for more information.
Size		●	
For custom features place an XX at the end of the part number and describe the special requirements (e.g. LPZ / 500 / XX - balanced to 10,000 rpm)			

ORDERING EXAMPLE	LPZ	6000	XX
Model	●		Special designation only (e.g. balancing, materials, etc.). Contact R+W for more information.
Size		●	
For custom features place an XX at the end of the part number and describe the special requirements (e.g. LPZ / 6000 / XX - balanced to 5,000 rpm)			

ORDERING EXAMPLE	LPA	800	250	41.28	38	XX
Model	●					Special designation only (e.g. special bore diameter tolerances, balancing, etc.). Contact R+W for more information.
Size		●				
Overall length (mm)			●			
Bore diameter Ø D1 H7				●		
Bore diameter Ø D2 H7					●	
For custom features place an XX at the end of the part number and describe the special requirements (e.g. LPA / 800 / 250 / 41.28 / 38 / XX - balanced to 15,000 rpm)						

ORDERING EXAMPLE	LPAI	800	237	25.4	50.8	XX
Model	●					Special designation only (e.g. special bore diameter tolerances, balancing, etc.). Contact R+W for more information.
Size		●				
Overall length (mm)			●			
Bore diameter Ø D1 H7				●		
Bore diameter Ø D2 H7					●	
For custom features place an XX at the end of the part number and describe the special requirements (e.g. LPA / 800 / 237 / 25.4 / 50.8 / XX - balanced to 15,000 rpm)						

**BIBUS**<sup>®</sup>  
 SUPPORTING YOUR SUCCESS

 BIBUS SK, s.r.o  
 Trnavská 31, SK-94 901 Nitra

 Tel.: 037/ 7777 911    Email: [sale@bibus.sk](mailto:sale@bibus.sk)  
 Fax.: 037/ 7777 999    <http://www.bibus.sk>