


SCP*2
 CMK2
 CMA2
 SCM
 SCG
 SCA2
 SCS
 CKV2
 CA/OV2
 SSD
 CAT
 MDC2
 MVC
 SMD2
 MSD*
 FC*
 STK
 ULK*
 JSK/M2
 JSG
 JSC3
 USSD
 USC
 JSB3
 LMB
 STG
 STS/L
 LCS
 LCG
 LCM
 LCT
 LCY
 STR2
 UCA2
 HCM
 HCA
 SRL2
 SRG
 SRM
 SRT
 MRL2
 MRG2
 SM-25
 CAC3
 UCAC
 RCC2
 MFC
 SHC
 GLC
 Ending

Compact/highly accurate actuator

Highly compact, accurate, and rigid LCM Series linear slide.
 ($\phi 4.5 / \phi 6 / \phi 8$)




● Ideal for high-accuracy positioning

Highly accurate 0.005 mm sliding parallelism and 0.03 mm installation parallelism are ensured, making this actuator ideal for positioning.

Sliding parallelism **0.005mm**
 0.03mm Installation parallelism

● Ultimate pursuit of downsizing

The cylinder, linear guide, and slide table have been integrated into a highly compact unit.



Linear Slide Cylinder LCM Series

SCP*2
CMK2
CMA2
SCM
SCG
SCA2
SCS
CKV2
CA/OV2
SSD
CAT
MDC2
MVC
SMD2
MSD*
FC*
STK
ULK*
JSK/M2
JSG
JSC3
USSD
USC
JSB3
LMB
STG
STS/L
LCS
LCG
LCM
LCT
LCY
STR2
UCA2
HCM
HCA
SRL2
SRG
SRM
SRT
MRL2
MRG2
SM-25
CAC3
UCAC
RCC2
MFC
SHC
GLC

Compatible with small spaces

This cylinder can be installed even in compact spacing, making layout more flexible.

Workpiece installation on either of two faces


The workpiece can be directly installed either on the table top or front using the installation holes provided.

Highly reliable stainless steel parts

Corrosion-resistant stainless steel is used for the cylinder and slide table.


Powerful design

A linear guide with contacts at four points enables this cylinder to be used with loads in different directions.



2 color switch mountable

The 2 color indicator type has been added for mounting onto the F-type miniature switch.



Wide variation

Available variations include adjustable stroke, side installation, and clean room specifications.

RoHS directive complied

Substances adversely affecting the environment, including lead and hexavalent chromium, have been eliminated.

RoHS

LCM Series products

	Series variation	Bore size	Stroke length (mm)			
			5	10	15	20
Double acting single rod type	LCM	φ 4.5 φ 6 φ 8	●	●	●	●
Double acting stroke adjustable type (extended)	LCM-P	φ 4.5 φ 6 φ 8	●	●	●	●
Double acting stroke adjustable type (extended/retracted)	LCM-R	φ 4.5 φ 6 φ 8	●	●	●	●
Double acting side installation type	LCM-A	φ 4.5 φ 6 φ 8	●	●	●	●
Double acting single rod type clean room specifications	LCM-P73	φ 4.5 φ 6 φ 8	●	●	●	●

Ending

Linear slide cylinder
Combined functions